- 1. All dimensions are in millimetres unless otherwise stated
- 2. Hoop should be attached to gate prior to excavation to mark out appropriate digging This also allows for check of how the structure will link into existing fencing or limitations.
- 3. Top of gate frame, gate and hoop to be level and vertical. On land subject to a slope some levelling of the ground may be needed around the structure prior to erection.
- 4. Post holes to be 150mm wide, and top of cross member to be 100mm below ground Where location may be used for lambing, base cross piece to be 175mm below ground level.
- 5. Gate to be set in concrete. If stock is in field, or public use expected shortly after installation, rapid set concrete to be used. Hoop support leas to be also set in concrete.
- 6. Where stock is only one side of fence, hoop to be placed on non-stock side where conditions allow. This may not be possible on some roadside locations.
- 7. Hoop must be not cause any impediment to other legitimate users of the land.
- Once erected, gate should be adjusted and checked for self-closing. Gate catch should also be free moving.
- 9. Gate hinge bolts to be made tamper proof.
- 10. Ensure post caps are in place.
- 11. Gates shall be obtained by the Contractor from:-Centrewire Ltd, Brookhouse Industrial Estate. Cheadle, Stoke - on - Trent, Staffordshire. ST10 1SR www.centrewire.com sales@centrewire.com
- or similar approved gates equal or exceeding the quality of 'Centrewire' gates.


Drawr


Ch'kd

Auth Date



GATE OPENING





Ground Level

1410 Post Ctrs

1210 Actual Leaf

in partnership with

262.5

260

240

202.5

www.viaem.co.uk Tel 0115 804 2100

Bilsthorpe Depot, Bilsthorpe Business Park, Bilsthorpe, Nottinghamshire, NG22 8ST

Highway Construction Details JLS 18/08/2020 Rights of way JD 16/02/2021 Woodstock' Kissing Gate For Medium Mobility Vehicles JΡ JLS SD/FP/13 0 N.T.S @A4

Rev.

Description

© Via East Midlands Limited, Registered in England no.09903246