



Bollard in verge

Bollard in footway

NOTES:

1. All dimensions are in millimetres unless otherwise stated.
2. Where a manufacturers foundation specification is in excess of the standard detail shown, the manufacturers details shall be used.
3. The bollard shall be adequately supported until the concrete has gained sufficient strength.
4. Bollards within 1 metre of the carriageway shall incorporate a red and white reflective band of 50mm width within the top 200mm of the bollard.
5. Bollards in footways
 - (a) The minimum bollard height above a footway surface shall be 900mm.
 - (b) Bollards in footways that are not within 1 metre of the carriageway shall incorporate a painted or fixed band (50mm wide) in a conspicuous colour within the top 200mm of the bollard.
 - (c) Where bollards are in an existing footway the reinstatement shall extend 150mm (min) outside the foundation.

Rev.	Description	Drawn	Ch'kd	Auth	Date



in partnership with
Nottinghamshire County Council
 www.viaem.co.uk Tel 0115 804 2100
 Bilsthorpe Depot, Bilsthorpe Business Park, Bilsthorpe,
 Nottinghamshire, NG22 8ST

Project		Highway Construction Details			Project	Drawn	Date
Status	Project No.	Kerbs, Footways And Pavings			JLS	JLS	18/06/2020
Drawing Title		Foundation For Square/Circular Section Bollards			Ch'kd	Auth	Date
Drawing No.		SD/11/26			JD	JP	31/07/20
					Rev.	Scale	
					0	N.T.S @A4	

Jul 31, 2020 - 11:15 am | H:\Highways\Design and Construction\Roads and Highways\Projects\06-192000020871 New Hwy Design Guide for New Dev\Design\CAD\New standard details\NCC SD/11/26 Foundation for Square_Circular Section Bollards.dwg