



SPECIFICATION

50 x 50mm RHS H-FRAME
 50 x 25mm RHS HANG & SLAM STILES
 DIA 45mm CHS TOP & BOTTOM RAILS
 DIA 30mm CHS OTHER RAILS
 76 x 76mm WELD MESH

NOTES:

1. All dimensions are in millimetres unless otherwise stated.
2. Gate should be placed on site and check to see how it will link into existing fencing or limitations.
3. Where stock is only on one side of fence the gate should open towards the livestock.
4. Gate must be level and vertical. On land subject to a slope some levelling of the ground may be needed around the structure prior to erection.
5. Post holes to be 150mm wide, and top of cross member to be 100mm below ground level.
6. Gate to be set in concrete. If stock is in field, or public use expected shortly after installation, rapid set concrete to be used.
7. Once erected, gate should be adjusted and checked for self-closing. Gate catch should also be free moving.
8. Gate hinge bolts to be made tamper proof.
9. Ensure post caps are in place.
10. Gates shall be obtained by the Contractor from:-
 Centrewire Ltd,
 Brookhouse Industrial Estate,
 Cheadle,
 Stoke - on - Trent,
 Staffordshire,
 ST10 1SR
www.centrewire.com
sales@centrewire.com
 or similar approved gates equal or exceeding the quality of 'Centrewire' gates.

| Rev. | Description | Drawn | Ch'kd | Auth | Date |
|------|-------------|-------|-------|------|------|
| | | | | | |
| | | | | | |



in partnership with



**Nottinghamshire
 County Council**

www.viaem.co.uk Tel 0115 804 2100
 Bilsthorpe Depot, Bilsthorpe Business Park, Bilsthorpe,
 Nottinghamshire, NG22 8ST

| | | | | | | | |
|---------------|-------------|---------------------------------------|--|--|---------|-------|------------|
| Project | | Highway Construction Details | | | Project | Drawn | Date |
| Status | Project No. | Right of Way | | | | JLS | 18/08/2020 |
| Drawing Title | | 'Chilton' Bridle Gate-One-Way Opening | | | | JD | 16/02/2021 |
| Drawing No. | | SD/FP/10 | | | | JP | JLS |
| | | | | | | 0 | N.T.S @A4 |