



**SPECIFICATION**

50 x 50mm RHS H-FRAME  
 50 x 25mm RHS GATE FRAME  
 50 x 50mm WELD MESH

**NOTES:**

1. All dimensions are in millimetres unless otherwise stated.
2. Gate should be placed on site and check to see how it will link into existing fencing or limitations.
3. Where stock is only on one side of fence the gate should open towards the livestock.
4. Gate must be level and vertical. On land subject to a slope some levelling of the ground may be needed around the structure prior to erection.
5. Post holes to be 150mm wide, and top of cross member to be 100mm below ground level. Where location may be used for lambing, base cross piece to be 175mm below ground level.
6. Gate to be set in concrete. If stock is in field, or public use expected shortly after installation, rapid set concrete to be used.
7. Once erected, gate should be adjusted and checked for self-closing. Gate catch should also be free moving.
8. Gate hinge bolts to be made tamper proof.
9. Ensure post caps are in place.
10. Gates shall be obtained by the Contractor from:-  
 Centrewire Ltd,  
 Brookhouse Industrial Estate,  
 Cheadle,  
 Stoke - on - Trent,  
 Staffordshire,  
 ST10 1SR  
 www.centrewire.com  
 sales@centrewire.com  
 or similar approved gates equal or exceeding the quality of 'Centrewire' gates.

Rev.	Description	Drawn	Ch'kd	Auth	Date
		JLS			18/08/2020
		JD			16/02/2021
		JP		JLS	
		0			Scale 1:1000 @A4



in partnership with



www.viaem.co.uk Tel 0115 804 2100

Bilsthorpe Depot, Bilsthorpe Business Park, Bilsthorpe,  
 Nottinghamshire, NG22 8ST

Project		Highway Construction Details			
Status	Project No.	Rights of Way		Drawn	Date
Drawing Title		'Marlow' Gate-One-Way Opening		Ch'kd	Date
Drawing No.		SD/FP/11		Auth	Traced
				Rev.	Scale
				0	1:1000 @A4