



- NOTES:
1. All dimensions are in millimetres unless otherwise stated.
 2. Softwood to be graded and pre-treated to meet BS 8417. All timber to have Forest Stewardship Council (FSC) Certification.
 3. Deck beams to be bolted to 'T' Section using 12mm diameter 'studding' bolts with nuts and washers both ends, cut off to length, burred to prevent undoing and ends painted with metal paint.
 4. This is drawing for decks of 6 - 9m only. For decks under 6m see Drg No SD/FP/16A. For further details of 'T' sections see Drg No SD/FP/18.
 5. Standard 'T' section precast concrete bank seat to be located in pre-dug hole and secured in ST3 concrete. Rapid set cement may be used.
 6. Treads (900mm x 300mm x 50mm) fixed with 4" galvanised (round) nails (oblique) 4 per tread.
 7. Railings to be galvanised steel tubing 48.3mm diameter (size 8) 'Kee Klamp' standard fittings (or suitable alternative) with galvanised finish to be used where joints or end fixings required. Railing height to be 750 - 900mm above bridge deck.

Rev.	Description	Drawn	Ch'kd	Auth	Date


 in partnership with


www.viaem.co.uk Tel 0115 804 2100
 Bilsthorpe Depot, Bilsthorpe Business Park, Bilsthorpe,
 Nottinghamshire, NG22 8ST

Project		Highway Construction Details			Project	Drawn	Date
Status	Project No.	Rights of Way			Ch'kd	JLS	18/08/2020
Drawing Title		6m-9m Timber Deck Foot-Bridge			Auth	JD	16/02/2021
Drawing No.		SD/FP/17			Traced	JP	JLS
					Rev.	0	Scale N.T.S @A4

Feb 16, 2021 1:32:44pm I:\Highways\Design and Construction\Roads and Highways\Projects\18-19\2000020971 New Hwy Design Guide for New Dev\Design\CAD\New standard details\NCC SD\ROW\SD/FP-17.dwg